

Auto Start Generator Control Panel

Panelsource

ENGINE & GENERATOR CONTROLS

P4X275 SERIES

STANDARD FEATURES

- Dimensions: 14"(w) x 9"(h) x 8"(d)
- ABS corrosion proof cabinet
- 2% accuracy ammeter, voltmeter, frequency meter and fusing
- Current transformers
- Volts/Amps phase selector switch
- DeepSea 703 automatic engine controller features automatic operation with speed sensing via generator output and with safety shutdowns for: low oil pressure, high water temperature, overspeed, underspeed, charge fail, overcrank, auxiliary inputs (qty 2), auxiliary outputs (qty 2) programmable for preheat, engine running, common warning, common shutdown, system in auto, common alarm and/or energize to stop
- Premium VDO engine gauge package includes oil pressure gauge, water temperature gauge, battery voltmeter, engine hourmeter, sender/switch combination
- Fuel, start and preheat relays
- Speed sensing via generator output (75-277Vac)
- Vibration isolators
- Corrosion resistant hardware
- Wiring diagrams



P4	___	___	___	___	___	X275
	1	2	3	4		
1. Voltage					3. PH/FRQ	
	A=480	B=380			A = 1/60	
	C=240-208	F=120			B=1/50	
					C=3/60	
2. Amps					D=3/50	
	(Format=amps/10)					
	(Example)					
	006=60amp				4. DC Volt	
	010=100amp				1=12	
	015=150amp				2=24	

PART NUMBER KEY

National Marketing and Distribution by Davidson Sales Co.

P.O. Box 9086, Daytona Beach, FL 32120

Phone: (386)274-2079 Fax: (386)274-2279 www.davidsonsales.com